

CAR

INCANDESCENT CHICAGO APPROVED RECESSED STEEL EMERGENCY UNIT



STANDARD



ILLUMINATION

- Two, 6V/12V 12.0 watt adjustable bi-pin halogen lamp heads.
- Long lasting, efficient, wedge base incandescent or bi-pin halogen lamps.
- High performance chrome-plated metallized reflector and glass lens for optimal light distribution.
- Adjustable 6V or 12V lamp heads provide optimal center-to-center spacing.

ELECTRICAL

- Dual 120V/277 voltage.
Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- LVD (low voltage disconnect) prevents battery from deep discharge.
- 6V sealed lead acid, maintenance-free, rechargeable battery.
- Remote capacity of 26.0 watt standard on 50.0 watt models.
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 120-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Designed for use with T-bar grid ceilings.
- Holes provided on enclosure for wire-suspension mount.


HOUSING

- Durable 20-gauge steel construction in white or black finish.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for two years.
- UL Listed for damp locations (20°C – 50°C).
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- Meets City of Chicago emergency light and plenum requirements.

DIMENSIONS



ORDERING INFORMATION

Sample Part Number: CAR-627

MODEL	VOLTAGE		WATTS (for 90 mins.)		HOUSING COLOR
CAR	6	6V	27	27 ¹	(blank) White
	12	12V	50	50	B Black

¹ Available in 6V only.

