LED A19 LAMP



Project:	
Type:	
Catalog #:	

STANDARD







APPLICATIONS

LED "A" lamps used for any incandescent "A" lamp replacement, long life maintenance free led replacement lamps.

ILLUMINATION

- Long life LEDs with up to 25,000 hours at 70% lumen maintenance.
- Choice of 2700K (±145), warm light, 4000K(±275), cool light, color temperature with 80 CRI.
- Produces 800-1100 lumens output from luminaire.
- Uses 1.18W high power, high quality LEDs.

ELECTRICAL

Dimmable to 10% with most dimmers.

Lutron Maestro C-L	MACL-153MR		
Lutron Skylark C-L	SCL-153P		
Leviton Sureslide	Cat.No.6674		
Lutron	PD-6WCL		
Legrand Harmony	HCL453PTCCCV6		

- Save 75% compared to incandescent sources
- High efficiency driver with a power factor ≥ .90 with input power of 120V, 50-60Hz
- Built-in LED Driver.
- Power consumption of 9 or 12 watts.
- Operation temperature of 20°C 40°C (-4°F 104°F).



MOUNTING

- Easy installation.
- No tools required for installation.

HOUSING

- Durable thermoplastic construction.
- E26 medium screw-base, Edison.

WARRANTY/LISTING

- Tested in accordance with IESNA LM79 & LM80.
- UL Listed for damp location.
- Passes FCC Class B.
- Five year warranty on all electronics and housing.

DIMENSIONS



ORDERING INFORMATION

MODEL	WATTS		KELVIN RATING		LUMENS	DIMMABLE OR NON
LEDA19	9W 9W	9 WATTS 9 WATTS	27K 4K	2700K 4000K	800 800	DIM DIM
	12W 12W	12 WATTS 12 WATTS	27K 4K	2700K 4000K	1100 1100	DIM DIM
LEDA19	9W 9W	9 WATTS 9 WATTS	27K 4K	2700K 4000K	800 800	NON-DIM NON-DIM
	12W 12W	12 WATTS 12 WATTS	27K 4K	2700K 4000K	1100 1100	NON-DIM NON-DIM